



Precision Plumbing Products

MINI-PRIME
BATTERY OPERATED TRAP PRIMER

www.pppinc.net

MINI-PRIME W/BOX

MPB-500-12V



ROUGH-IN DIMENSIONS
A. 12 INCHES
B. 12 INCHES
Depth 4 INCHES

| _____ B _____ | (cover not shown in photo).

MINI-PRIME

MP-500-12V



INLET: 1/2"NPT Male. ANSI/ASME B1.20.1.

OUTLET: 1/2"NPT Female. ANSI/ASME B1.20.1

WATER DISTRIBUTION: Distribution Units (DU Series) Drain Outlet: 5/8"OD and 1/2" OD Compression Fittings SAEJ512 1/2" female NPT ANSI/ASME B1.20.1.

SOLDER JOINTS: 95-5 lead free. Containing lead not in the excess of 0.2%.

ELECTRICAL COMPONENTS: Test Switch, Timer Solenoid Valve UL Listed.

TEMPERATURE/PRESSURE: 32°F-125°, 20 PSI-150 PSI. Minimum 2oz.water at 20 PSI per drain served.

ACCESS DOOR FOR MP-500 12V Model: D-814PC, D-814SS, F-814PC, F-814SS.

RECYCLE TIMER BOX: Dimensions - (L) 7 5/8"x (W) 4 5/8"x (D) 2 3/8"

PROJECT SUBMITTAL

Project: _____

Contractor: _____

Engineer: _____

Date Submitted: _____

Prepared By: _____

NOTE:

DESIGNED FOR USE WITH 1 TO 4 FLOOR DRAINS.
DISTRIBUTION UNITS PURCHASED SEPARATELY.

THE PRIMING VALVE MUST HAVE A MINIMUM
ELEVATION OF 12 INCHES (305MM) ABOVE THE
FINISHED FLOOR.

US PATENT NUMBER 5,797,419
CANADIAN PATENT NUMBER 2,174,578



Precision Plumbing Products

Division of JL Industries, Inc.

Airport Business Center
6807 NE 79th Court, Suite E
Portland, Oregon 97218

T (503) 256-4010
F (503) 253-8165

www.pppinc.net

